



magfix
FIXING BRILLIANCE

FIXING IT FOREVER

magfix
FIXING BRILLIANCE

- Unlocking Possibilities, Empowering Industries: Magma, a trailblazer in B2B manufacturing services, stands at the forefront of innovation, catering to a diverse spectrum of over 200 industries across Asia. With a robust backbone supported by global venture capital firms, our footprint spans procurement and logistics operations across 12 states in India.
- **At Magma**, we redefine industry dynamics through our comprehensive verticals:
 - Factory Digitization Tools
 - Input Materials
 - Industrial Gases
 - Chemicals
 - Petroleum
 - Logistics & Exports
- We don't just meet industry standards; we set them. Our commitment to excellence, coupled with cutting-edge solutions, ensures that Magma is not just a service provider; it's a strategic partner in your journey toward Growth.
- Join hands with Magma — Where Innovation Meets Industry.



FIXING
IT FORVER



TILE ADHESIVE

Tile fixing adhesive for
internal wall & floor application

Packing 20kg

PRODUCT DETAILS

MagFix Eco is a grey, high polymer modified, cement-based tile adhesive that is suitable for fixing tiles, ceramic and Vitrified tiles in interior situations. Consult Magma regarding the use of a higher-performance adhesive for applications in difficult and demanding situations.

SIZE: 30x45, 30X60, 60x60cm, etc.

SHELF LIFE & STORAGE

Shelf life is 12 months from the date of manufacturing in unopened condition. Store in a cool & dry place.

COVERAGE

This will depend on the nature and lateness of the surface and the method of application but at 3mm thickness it is approximately 55-60 sq. ft. per 20kg bag when using a thin-bed trowel. For good coverage, all surfaces must be clean, smooth, plumb, level, and free from defects & undulations.

PROPERTIES	RESULTS
Appearance	Powder Grey
Mixing Ratio	4 to 6 ltr. clean water mix with 20kg
Adhesive Thickness	3 to 10mm
Open Time	20 min at 20°C
Adjustability Time Pot Life	20 min at 20°C
Trafficable Time	24 Hours
Shear Adhesion (as per annex B) Dry Condition	>1000 KN/mm ²
Tensile Adhesion (as per annex A) Dry Condition	>800 KN/mm ²
EN 12004 Standard	CITE

PRODUCT DETAILS

Magfix Ultra is a cement-based tile adhesive for floor and wall tiles, suitable for fixing large sizes of tiles in interior and exterior uses. This is ideal for fixing tiles on tiles.

SIZE: 60x120, 80x160, 120x180cm, etc.

SHELF LIFE & STORAGE

Shelf life is 12 months from the date of manufacturing in unopened condition. Store in a cool & dry place.

COVERAGE

This will depend on the nature and lateness of the surface and the method of application but at 3mm thickness it is approx. 55-60 sq. ft. per 20kg bag when using a thin-bed trowel. For good coverage, it is important that all surfaces should be clean, smooth, plumb, level and free from defects & undulations.

PROPERTIES	RESULTS
Appearance	Powder Grey/White
Mixing Ratio	4 to 6 ltr. clean water mix with 20kg
Adhesive Thickness	3 to 15mm
Open Time	20 min at 20°C
Adjustability Time	20 min at 20°C
Trafficable Time	24 Hours
Shear Adhesion (as per annex B) Dry Condition	>1250 KN/m ²
Tensile Adhesion (as per annex A) Dry Condition	>1050 KN/m ²
EN 12004 Standard	C2TE



FIXING
IT FOREVER



TILE ADHESIVE

Tile fixing adhesive for
internal & external wall and floor application

Packing 20kg



FIXING
IT FORVER



STONE ADHESIVE

Tile and stone fixing adhesive for
internal & external wall and floor application

Packing 20kg

PRODUCT DETAILS

MagFix Supreme is a premium, water & frost resistant, highly polymer modified cementitious wall and floor tile adhesive specially formulated for fixing mosaic tiles ceramic, glass mosaic etc. It is also suitable for fixing ceramic, vitrified wall & floor tiles, metal or glass tiles, marble, granite and other natural stone in interior and exterior locations which includes use in swimming pools. This is ideal for fixing tile on tile.

SIZE: 120x180,120x240,80x140cm, etc.

SHELF LIFE & STORAGE

Shelf life is 12 months from the date of manufacturing in unopened condition. Store in a cool & dry place.

COVERAGE

This will depend on the nature and lateness of the surface and the method of application but at 3mm thickness it is approx. 55-60 sq. ft. per 20kg bag when using a thin-bed trowel. For good coverage, it is important that all surfaces should be clean, smooth, plumb, level and free from defects & undulations.

PROPERTIES	RESULTS
Appearance	Powder Grey/White
Mixing Ratio	4 to 6 ltr. clean water mix with 20kg
Adhesive Thickness	3 to 18mm
Open Time	20 min at 20°C
Adjustability Time	20 min at 20°C
Trafficable Time	24 Hours
Shear Adhesion (as per annex B) Dry Condition	>1700 KN/m ²
Tensile Adhesion (as per annex A) Dry Condition	>1400 KN/m ²
EN 12004 Standard	C2TE

PRODUCT DETAILS

MagFix Supreme Plus is highly polymer modified cementitious wall and floor tile adhesive specially formulated for fixing mosaic tiles ceramic, glass mosaic etc. It is also suitable for fixing ceramic, vitrified wall & floor tiles, metal or glass tiles, marble, granite, quartz stone, terrazzo and other natural stone in interior and exterior locations which includes use in swimming pools.

SIZE: 120x240,120x180,160x320,80x240,80x300cm, etc.

SHELF LIFE & STORAGE

Shelf life is 12 months from the date of manufacturing in unopened condition. Store in a cool & dry place.

COVERAGE

This will depend on the nature and lateness of the surface and the method of application but at 3mm thickness it is approx. 55-60 sq. ft. per 20kg bag when using a thin-bed trowel. For good coverage, it is important that all surfaces should be clean, smooth, plumb, level and free from defects & undulations.

PROPERTIES	RESULTS
Appearance	Powder Grey/White
Mixing Ratio	4 to 6 ltr. clean water mix with 20kg
Pot Life	20 min at 20°C
Open Time	20 min at 20°C
Adjustability Time	45 min.
Trafficable Time	24 Hours
Shear Adhesion (as per annex B) Dry Condition	>3500 KN/mm ²
Tensile Adhesion (as per annex A) Dry Condition	>2900 KN/mm ²
EN 12004 Standard	C2TES1



FIXING
IT FOREVER



STONE ADHESIVE

Tile and stone fixing adhesive for
internal & external wall, floor and ceiling application

Packing 20kg



FIXING
IT FORVER



BLOCK JOINTING

For interior and exterior use for
**Preparing thin bed block mortar for AAC
and cellular concrete blocks**

Packing 40kg

PRODUCT DETAILS

Magfix Block Jointing is a factory prepared blend of carefully selected raw materials, Portland cement, graded aggregates and polymers. Designed for use with water to produce high strength thixotropic mortar ideal for laying aerated light weight concrete, fly ash bricks, cement hollow blocks, cellular concrete blocks or smoothing over the block work surface in layers of up to 12mm thickness that meet and exceed the requirements of National and International Standards.

SHELF LIFE & STORAGE

Shelf life is 12 months from the date of manufacturing in unopened condition. Store in a cool & dry place

ADVANTAGES

- Superior durability
- No curing required after block work is done
- Improved adhesion between two blocks
- Fast & economical

COVERAGE

Approximately 100-130sq.ft. per 40kg bag. Coverage is based on smoothness and evenness of the substrate, size of blocks used and the thickness of mortar used. A general guideline for coverage of mortar is given when used with 25% water added to powder.

PROPERTIES	RESULTS
Appearance	Powder Grey
Water Demand	10 to 30%
Pot Life	Approx 2 hour
Hard Dry	24 Hours
Compressive Strength	>15 N/mm ² @28 Days
Tensile Strength	>0.8 N/mm ² @28 Days

PRODUCT DETAILS

Magfix Tile Grout is a high quality fine, polymer modified, water-resistant, cement based powder grout designed for grouting glaze wall tiles, mosaics, vitrified & fully vitrified tiles, floor tiles and industrial floor tiles.

SHELF LIFE & STORAGE

Shelf life is 24 months from the date of manufacturing in unopened condition. Store in a cool & dry place

COLORS



White



Pink



B. Beige



Ivory



Magenta



Jaisalmer



Grey



Black



C. Brown



S. Blue



O. Green



R. Brown



V. Terracotta



D. Grey



FIXING
IT FOREVER



TILE GROUT

For interior and exterior use for preparing thin bed block mortar for AAC and cellular concrete blocks.

Packing 500gm | 1kg



magfix

FIXING BRILLIANCE



OUR PRODUCTS

An initiative of  Magma

Customer Care: +91 99090 49392

E-mail : info@magemagroup.in

Disclaimer: The product information & application details given by the company & its agents has been provided in good faith & meant to serve only as a general guideline during usage. Users are advised to carry out tests & take trials to ensure on the suitability of products meeting their requirement prior to full scale usage of our products. Since the correct identification of the problems, quality of other materials used and the on-site workmanship are factors beyond our control, there are no expressed or implied guarantee / warranty as to the result obtained. The company does not assume any liability or consequential damage for unsatisfactory results, arising from the usage of our products.

magfix
FIXING BRILLIANCE